Fitting for 2 top-running wooden doors up to 16 kg (35 lbs.), with screwed on or groove mounted running track. With soft and self closing mechanism. Design Inslide.

Product highlights

ς


11

난 Comfort	Smooth, silent running with Comfort Roller and soft
	and self closing system for different door weights


Productivity Efficient thanks to tool-less door installation as well as easy, intuitive adjustment

Technical specifications

\triangle	Max.	16 kg (35 lbs.)
${}^{\uparrow}_{\downarrow}$	Max.	1400 mm (4'7 1/8'')
$\stackrel{\leftarrow}{=}$	Max.	1000 mm (3'3 3/8'')
→[]←		16–19 mm (5/8'' to 3/4'')



Installation examples



Subject to technical modifications. Metric specifications are exact. Inches are approximate.



Set for 2 wooden doors up to 16 kg (35 lbs.), with height adjustment

			No.
Hawa Clipo 16 H	HIS, for 2 doors		053.3220.071
Set consisting	of:	053.3220.071	No.
	Hawa Clipo 16 H/Hawa Regal 16 C running gear, plastic, anthracite	4	053.3205.071
and and a second	Hawa Clipo 16/Hawa Regal 16 C stopper, plastic, gray	2	053.3215.071
et te	Housing, plastic, anthracite	4	053.0183.001
S.	Fillister head screw, 3.5x16 mm (5/32"x5/8"), steel, zinc-plated	8	766.6052.100
	Door follower, plastic, anthracite	1	053.3217.071
SI >	Flat countersunk head chipboard screw, 4.5x16 mm (3/16"x5/8"), steel, zinc-plated	2	600.0000.478
	Hawa Clipo 16 H bottom guide, plastic, anthracite	2	053.3214.001

Running tracks

		mm (inch)	No.
		2,500 (8' 2 7/16'')	053.3229.250
	A: Single running track, for glue fixing, aluminum	3,500 (11' 5 25/32'')	053.3229.350
*		6,000 (19' 8 7/32'')	053.3229.600
	B: Single running track, with swivel-lug, aluminum (not for hard wood/MDF)	2,500 (8' 2 7/16'')	053.3227.250
	B: Single running track, with swivel-lug,	3,500 (11' 5 25/32'')	053.3227.350
	aluminum	6,000 (19' 8 7/32'')	053.3227.600
		2,500 (8' 2 7/16'')	053.3225.250
	C: Single running track, aluminum, pre-drilled	3,500 (11' 5 25/32'')	053.3225.350
		6,000 (19' 8 7/32'')	053.3225.600
		2,500 (8' 2 7/16'')	053.3226.250
	D: Double running track, aluminum, pre-drilled	3,500 (11' 5 25/32'')	053.3226.350
	p.o. a.mou	6,000 (19' 8 7/32'')	053.3226.600
		2,500 (8' 2 7/16'')	053.3231.250
	E: Double running track, aluminum, anodized, pre-drilled	3,500 (11' 5 25/32'')	053.3231.350
¥		6,000 (19' 8 7/32'')	053.3231.600

Track end piece set for single running tracks

				No.	
Track end piece	Track end piece, for screw fixing, plastic, gray				
Track end piece	, with swivel lug, plastic, gra	ay		053.3211.081	
Set consisting	of:	053.3210.081	053.3211.081	No.	
	Track-end piece, for screw fixing, plastic, grey	2		053.3210.001	
	Track-end piece, with swivel lug, plastic, grey		2	053.3211.071	

Guide tracks

		mm (inch)	No.
		2,500 (8' 2 7/16'')	053.3012.250
6	Guide track, groove width 7 mm (9/32''), plastic, anthracite	3,500 (11' 5 25/32'')	053.3012.350
		6,000 (19' 8 7/32'')	053.3012.600

Soft close up to 8/16 kg (17/35 lbs.)

				No.
Soft close Hawa Clipo 16/Hawa Regal C 16, up to 8 kg (17 lbs.)			053.3332.071	
Soft close Hawa up to 16 kg (35 l	a Clipo 16/Hawa Regal C 16 bs.)	,		053.3332.072
Set consisting	of:	053.3332.071	053.3332.072	No.
G	Damper, up to 8 kg (17 lbs.)	2		053.3330.071
	Trigger, with stopper	2	2	053.3331.071
El S	Cross recessed pan head screw, 2.2x8 mm (3/32"x5/16"), steel, zinc-plated	2	2	600.0000.482
COLUMN TO A	Damper, up to 16 kg (35 lbs.)		2	053.3330.072

Guide tracks 4-point guidance

	mm (inch)	No.
Single guide track, for glue fixing, aluminum, anodized	6,000 (19' 8 7/32'')	053.3296.600

Components 4-point guidance

		No.
en e	Bottom guide Hawa Clipo IS/Hawa Regal C 16, plastic, anthracite	040.3124.071
P	Stopper guide track, plastic, grey	053.5094.071

Door centering


			No.
Door centering,	plastic, anthracite, for 2 doors		053.3207.071
Set consisting of:		053.3207.071	No.
Ð	Housing door centering, plastic, anthracite	2	053.5014.001
	Pin door centering, plastic, anthracite	2	053.0171.001
\bigcirc	Rubber buffer, plastic, grey	1	025.0107.001

Accessories


	No.
Housing Hawa Clipo 16, press-fit, plastic, anthracite	083.3009.002
Track cleaner, plastic, red	040.3142.071




Further installation examples




Calculations



4 point guidance




Housing for press-fitting



Door centering

()



Soft close

	Z	≥			
	1	2			
Hawa Clipo 16 H IS	1'3 <u>3</u> "	1' 11 5 "			
Hawa Clipo 16 H MS	1' 5 <u>1</u> "	2' 1 1 "		Z	2
Hawa Clipo 16 H FS	1' 5 <u>1</u> "	2' 1 1 "		1	2
Hawa Clipo 16 HM IS	1' 3 <u>3</u> "	1' 11 5 "	Hawa Clipo 16 H IS	400	600
Hawa Clipo 16 GK IS	1' 3 <u>3</u> "	1' 115"	Hawa Clipo 16 H MS Hawa Clipo 16 H FS	438 438	638 638
Hawa Clipo 16 GS IS	1' 3 <u>3</u> "	1' 115"	Hawa Clipo 16 HM IS	400	600
Hawa Clipo 16 GPK IS	1' 3 <u>3</u> "	1' 11 ⁵ "	Hawa Clipo 16 GK IS Hawa Clipo 16 GS IS	400 400	600 600
Hawa Clipo 16 GPPK IS	1' 3 <u>3</u> "	1' 11§"	Hawa Clipo 16 GPK IS Hawa Clipo 16 GPPK IS	400 400	600 600

	$\geq 10\frac{10}{4}$	
	Z	
-		

> 260

~		
	≥ 460	
	$\geq 1^{1}-6_{8}^{1*}$	
	Z	

Accessories

DCS

- Straightening fitting from page 266

Planning/execution

Further information about the product can be found on www.hawa.com.