

Standard-Duty Cylindrical Grade 2 Leversets



Standard Features

Performance Complies with ANSI A156.2, Series 4000, Grade 2, 400,000 cycles, ANSI A117.1

accessibility (ADA) code, UL/ULC listed for 3 hour fire door

Chassis Cylindrical, steel-coated w/ zinc dichronate (corrision resistance)

Lever Non-handed

Latch 1-1/8" x 2-1/4" square corner faceplate, 3/4" housing, 1/2" throw (stainless steel)

Rose 3-1/4" diameter

Thru-bolts Removable thru-bolts standard

Backset 2-3/8" or 2-3/4"

Strike Square corner 1-1/4" x 4-7/8" ANSI ASA Strike

Standard Cylinder Standard cylinder Schlage (SCC) - 6-pin solid brass, C keyway, keyed different (KD).

Kevs Two nickel silver per lock

Door Range 1-3/8" to 2"

Door Preparation 2-1/8" diameter for bore, 1" diameter latch bore. Fits standard 161 door prep.

Warranty 1 year limited

Optional Features

Chassis Freewheeling clutch, optional for Cortland and Sturdee only.

Strike **T Strike** (1-1/8" x 2-3/4"), and **F Strike** (full lip)

Keying Options

Tell Cylinder Restricted Tell keyway cylinder can key both the cylinder and interchangeable core in

> one lock. The cylinders and IC cores are interchangeable. Tell keyway cylinder is available only keyed to 6-pin. Tell IC cylinder can be keyed to 6-pin or 7-pin

interchangeable core (IC).

Other Cylinder

Options

Arrow A (ARA), Corbin 59A1 (C059A1), Corbin 60 (C06), Corbin Russwin L4 (CL4), Kwikset (KW1), Russwin D1 (RD1), Sargent LA (SAL), Schlage E (SCE), Schlage F

(SCF), Weiser E (WRE), Yale 8 (YA8), Yale GA (YGA)

ALL CYLINDERS 6-PIN. CAN ALSO BE PINNED 5-PIN.

IC Keyway Cylinder

Tell, Best A (BA), Best B (BB), Best C (BC), Best D (BD), Best E (BE), Best F (BF), Best G AVAILABLE 6- OR 7-PIN (BG), Best H (BH), Best J (BJ), Best K (BK), Best L (BL), Best M (BM), Best Q (BQ), Best

U (BU), Black construction core (BLK), Less core (00), Not specified (XX)

Keying Options Grand master key (GMK), construction master key (CMK), master key (MK), keyed

different (KD), keyed alike (KA), interchangeable core uncombinated (IC), 0-bitted (0BIT)

TELL MANUFACTURING, INC — Page 29 — 2014

Corporate Office: 18 Richard Drive, Lititz, PA 17543 Toll Free: 800-433-4047 Phone: 717-625-2990 Fax: 717-625-7095 OTHER LOCATIONS: BIRMINGHAM, ALABAMA MIRA LOMA, CALIFORNIA ELKHART, INDIANA HOUSTON & DALLAS, TEXAS

WEBSITE: www.tellmfg.com



LC2600 Series Function Chart

FUNCTION	FUNCTION No.	OUTSIDE INSIDE	FUNCTION DESCRIPTION	ANSI NO.
Entry/Office	81		 Latchbolt operated by lever from either side Outside lever locked by turn button from inside Unlocked by key from outside or rotating inside lever 	F82
Entry	82		 Latchbolt operated by lever from either side Outside lever locked by push button from inside Outside unlocked by key from outside or rotating inside lever 	F82
Classroom	84		 Latchbolt operated by lever from each side Outside lever locked or unlocked by key from outside Inside lever always operates latch 	F84
Storeroom	86		 Latch operated by rotating inside lever or key in outside lever Outside lever always fixed 	F86
Communicating	91		 Deadlocking latchbolt operated by either lever Key in outside lever; locks / unlocks outside lever Key in inside lever; locks / unlocks inside lever Each lever locks / unlocks independently 	F80
Privacy Bedroom/Bathroom	76		 Latchbolt operated by lever from either side Outside lever locked by push button on inside Unlocked by emergency release on outside, rotating inside lever, or closing door 	F76
Passage/Closet	75		■ Latchbolt operated by lever from either side at all times	F75
Single Dummy	01		■ Pull lever one side ■ No mechanical operation	



ACCESSORIES

LC2600 Series Strikes

CL100186 — ASA Strike, US32D **CL100187** — ASA Strike, US3

CL100415 — ASA Strike, US10B

CL100191 — T Strike, US32D

CL100189 — T Strike, US3

CL100420 — T Strike, US10B

For metal frames. (1-1/4" x 4-7/8" x 3/32"). For wood frames. (1-1/8" x 2-3/4" x 3/32"). For wood residential applications.

CL100190 — F Strike, US32D

CL100192 — F Strike, US3

CL100581 — F Strike, US10B

(1-5/8" x 2-1/4" x 3/32").







LC2600 Series Non-**Restricted Keyway**

CL100219 ---

Cylinder, Schlage C, US26D

CL100584 —

Cylinder, Schlage C, US4

Standard brass 6-pin cylinder SCC keyway, optional keyways available (see price list).



LC2600 Series Tell **Restricted Keyway**

TELL CYLINDERS:

CL101503 --6 pin Tell cylinder, US26D

CL101504 —

6 pin Tell cylinder, US4



FINISHES: US32D=Satin Stainless Steel, US3=Bright Brass, US26D=Satin Chrome, US10B=Oil Rubbed Bronze

WEBSITE: www.tellmfg.com



How to Order LC2600 Series

