

HALI CONTEMPORARY INTERCONNECT

The perfect solution for multi-family housing, Interconnect provides quality, security and style while meeting ADA requirements and fire code ratings.

- Features SmartKey Security™ Re-key Technology with BumpGuard™ Protection
- Lifetime mechanical and finish warranty
- Lever options are in compliance with the American National Standards Institute (ANSI A117.1) and the Americans with Disabilities Act (ADA)
- Meets fire code rating for emergency panic exit

Interconnect Specifications

Door Prep	2 ½" diameter face hole & 1" diameter latch hole
Backset	DB: Adjustable to 2 3/8" or 2 3/4" Lever: Fixed 2 3/8" or Fixed 2 3/4"
Door Thickness	Door Kits Available
Cylinder	SmartKey [™] on 780 Deadbolt and Smartkey [™] on KCDB SQT
Faceplates	Square or round corner
Strikes	Round corner strike, round corner with full lip, square metal jam and square corner strike
Door Handing	Reversible
ANSI/BHMA	Grade 3
ADA	Lever options are in compliance with the American National Standards Institute (ANSI A117.1) aand the Americans with Disabilities Act (ADA)
UL	Meets 3 hour fire rating.

Finishes



Satin Nickel 15




Matte Black 514




Polished Chrome 26

Dimensions



Design	Α	В	С	D	E	F
Interior	1 13/32"	1 3/4"	9 3/16 "	2 7/16"	5 1/2"	2 27/32"



Design	Α	В	С	D	E
508HRL KCDB	1 5/16"	2 31/32"	5 ½"	2 1/4"	2 67/100"
508HRL	1 5/32"	2 5/8"	5 ½"	2 1/4"	2 67/100"



Re-Key Your Lock Yourself in Seconds










90°





Insert the key that currently operates your lock, and rotate it 90° clockwise.



Insert the SmartKey tool fully and A Insert the SmartKey hole.

B Remove the SmartKey tool and the current key.





A Fully insert your new key into the lock, and rotate it 180°.

B) Rotate the new key 90° back to the starting position, and remove it. Your lock is now re-keyed to your new key, and your old key will no longer operate the lock.

