

TOLERANCE TABLE

SPECIFIED DIMENSION IN INCHES	METAL DIMENSIONS		SPACE DIMENSIONS				
	ALLOWABLE DEVIATION FROM SPECIFIED DIMENSION WHERE 75 PERCENT OR MORE OF THE DIMENSION IS METAL		ALLOWABLE DEVIATION FROM SPECIFIED DIMENSION WHERE MORE THAN 25 PERCENT OF THE DIMENSION IS SPACE				
	All except those covered by column 3	Wall thickness (4) completely (5) enclosing space 0.11 sq. in. and over (eccentricity)	At dimensioned points 0.250-0.624 inches from base of leg	At dimensioned points 0.625-1.249 inches from base of leg	At dimensioned points 1.250-2.499 inches from base of leg	At dimensioned points 2.500-3.999 inches from base of leg	At dimensioned points 4.000-5.999 inches from base of leg
Col. 1	Col. 2	Col. 3	Col. 4	Col. 5	Col. 6	Col. 7	Col. 8
	Standard Tolerance	Standard Tolerance	Standard Tolerance	Standard Tolerance	Standard Tolerance	Standard Tolerance	Standard Tolerance
UP THRU 0.124	0.006	+ - 15% OF SPECIFIED DIMENSION, + - .090 MAX + - .025 MIN.	0.010	0.012
0.125-0.249	0.007		0.012	0.014	0.016
0.250-0.499	0.008		0.014	0.016	0.018	0.020	..
0.500-0.749	0.009		0.016	0.018	0.020	0.022	..
0.750-0.999	0.010		0.018	0.020	0.022	0.025	0.030
1.000-1.499	0.012		0.021	0.023	0.026	0.030	0.035
1.500-1.999	0.014		0.024	0.026	0.031	0.036	0.042
2.000-3.999	0.024		0.034	0.038	0.048	0.057	0.068
4.000-5.999	0.034		0.044	0.050	0.064	0.078	0.094